

WEB SPEED DOME CAMERA DOH-240SiW/ SEW



Built-in 22x Day & Night Camera Dual Streaming

220X Auto Focus Zoom Lens and Mpeg 4 Web Server built inside will allow you to conduct easy surveillance from Remote Area

FEATURES

- 22X Optical Zoom Lens Integrated Web Speed Dome Camera
- Day & Night, Minimum Illumination 0.01Lux
- MPEG4 Compression with MPEG4, Multi-Streaming
- Dynamic IP supported
- High Resolution Image can be remotely sent (704(H) X 480(V))
- User Friendly and Easy Surveillance, Monitoring, Searching, Control from Local or Remote Area

SPECIFICATIONS

MODEL	DOH-240Siw / Sew	
Signal system	NTSC	PAL
Image sensor	1/4" Type Sony HAD CCD	
Number of effective pixels	768(H)×494(V) 380K	752(H)×582(V) 440K
Horizontal resolution	More than 480 TV lines	More than 450 TV lines
Lens	22x Optical zoom, F 1.6(Wide) -3.8(Tele), f=3.9-85.8mm	
Minimum illumination	1.0 Lux (30 IRE, AGC34dB), 0.1Lux(day&Night), 0.01Lux(DSS)	
Luminance S/N ratio	More than 49dB (AGC OFF)	
Focus mode	Auto / manual / oneshot	
BLC Control	BLC Level (0-80)	
AGC Control	Auto / 8-38 dB selectable	
Shutter speed control	1/60-1/10,000 sec 28 steps	1/50-1/10,000 sec 28 stps
Flickerless set	Off/On(1/100 sec shutter set)	Off/On(1/120 sec shutter set)
Sharpness control	Level 0-15	
Pan/Tilt speed	Max Pan : 180°/sec / Tilt 90°/sec	
Vertical Tilt	+2° -90°	
Home position	On / Off	
Preset point	128 Presets	
Video Output	Channel 1 ch Compression MPEG4 Resolution 704 × 480 Frame rate 30 fps	
Audio (Additional Option)	Bi-directional Compression G,723	
View Program	PC, PDA, Mobile phone	
Network	Global/Private/Static/Dynamic IP DDNS Support Encryption (ID/Password/Image) Interface (10/100Mbps)	
Recording	Manual / Schedule / motion Detection / Sensor Event	
Event & Alarm	Sensor Trigger /Motion Detection / Alarm Notification	
Connectors	RJ 45, Power supply	
API Support	Available	
Environment	DOH-240SiW(Indoor) / DOH-240SeW(Outdoor)	
Operating temperature	DOH-240SiW(-10°C to 50°) DOH-240SeW(-40°C to 50°)	
Weight	About 3.2Kg(DOH-240Siw) / 5.2Kg(DOH-240SeW) (Without adaptor)	
Material	ABS(Si), Aluminum(Se), 6.6 inch Bubble (Poly-carbonate)	
Demension	240Siw (224(H) × 189(D)mm), 240SeW (271(H) × 217(D)mm)	
Color	Back box (ivory), Clear Bubble	
Input Voltage	18~30 VAC, AC24V (nominal), Fuse 1.5A	
Power Consumption	25W (Max)	

IP Speed Dome Camera Configuration

